

Product Specifications

FlashLink® Real-Time In-Transit Logger

Temperature Range	-4°F to 131°F (-20°C to 55°C)
Temperature Accuracy	±0.6°F (0.3°C) over full temperature measurement range
Temperature Resolution	0.015°F/°C
Humidity Measurement Range	0% to 100% RH
Humidity Accuracy	±2% from 0% RH to 90% RH ±3% from 90% RH to 100% RH stated within temperature exposure range of 41°F to 131°F (5°C to 55°C), non-condensing
Humidity Resolution	0.01% RH
Light Sensor	Dual Stage Sensor
Shock Sensor	3-axis G sensor
GSM Network	Quad band GSM 850/900/1800/1900 MHz
SIM	Global data roaming
Power Source	Lithium-ion Battery
Battery Life	12 month shelf life (non-active)
Weight	7.76 oz (220 grams)
Logger Dimensions	4.92 in Dia. x 1.18 in (125 mm Dia. x 30 mm)
Waterproof Rating	IP54
Certification	FCC, CE Mark, Temperature & Humidity Sensor NIST traceable



Models	Duration	Logging Interval & Data Upload
22300	25-Day	15 Min
22301	100-Day	60 Min

- Monitors location, temperature, humidity, light, shock
- Data transmitted via GSM cellular networks
- No need to open vehicle doors to access information
- 24/7 cloud service to view and analyze data remotely
- Make immediate cold chain management decisions
- Reroute trucks when necessary
- Customize settings for high/low alarm limits
- Data stored in the cloud for traceability, audits, HACCP, and FSMA compliance

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 22300 17H3

