

PRODUCT SPECIFICATIONS

FlashLink® USB Logger In-Transit Data Logger



- Large, easy to read LCD display
- Trip history statistics available on LCD
- Single-use
- USB Connection
- NIST traceable and CE Mark
- IP54 water-resistant rating
- Download data as PDF report with free FlashPDF software
- Patented Shadow Log feature guarantees data even if the operator fails to start the unit

| Recording Period | Models | | Logging Intervals |
|------------------|--------|-------|-------------------|
| | °F | °C | |
| 5-day | 20910 | 20914 | 1 min 54 sec |
| 15-day | 20911 | 20915 | 5 min 40 sec |
| 45-day | 20912 | 20916 | 16 min 58 sec |
| 75-day | 20913 | 20917 | 28 min 16 sec |

DeltaTRAK's FlashLink USB Logger is the ideal device for documenting storage and transport conditions of temperature-sensitive products.

| | |
|----------------------------------|--|
| Measurement Range | -40°F to 149°F (-40°C to 65°C) |
| Temperature Resolution | 0.1°F/°C |
| Accuracy | ±1.0°F from 14°F to 77°F (±0.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C) |
| Data Capacity | 3823 points |
| Data Download Time | 2 seconds typical for 3823 points |
| Factory Programable Alarm Levels | High & Low levels over entire range, displayed on LCD |
| Battery | (CR2032) 3.6V Lithium/18 months |
| Dimensions/Body | 1.575" x 3.189" x .575" (40mm x 81mm x 13mm) |
| Casing | PC/ABS plastic |
| Weight | 1.3 oz. (36 grams) |
| Shock Resistance | Withstands 3-foot (1 meter) drop to hard surface |
| Certification | CE Mark, NIST traceable, ROHS Compliant |
| Display | LCD, Red LED Alarm |
| IP Rating | IP54 Splashproof (with silicon cap on) |
| Storage conditions | -4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation |
| Min. System Requirements | Windows PC with XP, or higher |
| Download Requirements | Direct USB connection to PC. View data with free FlashPDF software downloaded from our web site, and Adobe Reader 7.0 or higher |

DeltaTRAK manufactures products under an ISO 9000 registered quality management system

SS0078_11L2



DeltaTRAK

1-800-962-6776

• **www.deltatrak.com**

P.O. Box 398 • Pleasanton, CA 94566 • Tel: (925) 249-2250 • Fax: (925) 249-2251